

DECLARATION OF PERFORMANCE

No. COTTO 001

- Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$
- Intended use(s)
For internal and external walls and floorings
- Name or registered trade mark, and contact address of the manufacturer
THAI CERAMIC CO. LTD.,
1 Siam Cement Road. - 10800 Bangkok-Bangsue - Thailand
- System(s) of assessment and verification of constancy of performance (AVCP)
System 4
- Name and identification number of notified laboratory, if relevant – **Not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue **18 MAY 2015.**
- Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	Based on the decision 96/603/CE and its changes EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1300 N	
Slipperiness	See table attached	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	



The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

MR. PANU VADRUGCHIT ; TECHNICAL OFFICE MANAGER

Name and function

18 MAY 2015



Allegato alla Dichiarazione di Prestazione
 Attachment to Declaration of Performance
 Annexe à la déclaration de performance
 Anhang der Leistungserklärung
 Anexo a la Declaración de Performance
 Załącznik do deklaracji właściwości użytkowych
 A Teljesítmény Nyilatkozat kiegészítő táblázata

No. COTTO 001

Tabella - Scivolosità (dove richiesto dalla legislazione)
 Table - Slipperiness (where required by regulation)
 Table - Glissement (si requis par la loi)
 Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)
 Tabla - Deslizamiento (donde sea requerido por ley)
 Tabela - Poślizgowosc (gdzie wymagane przez prawo)
 Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)

Rev. 0 del/of/de/vom/de/a 18 MAY 2015

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka

COTTO

Serie / Series / Kolekcja	CEN/TS 16165:2012 Annex B α_{SHOD}	BCRA D.M. 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
BALZA naturale	α da 11° a 19°	> 0,4	R10	N.P.D.
BALZA grip	α da 20° a 27°	> 0,4	R11	N.P.D.
NEO BASALT soft	α da 6° a 10°	N.P.D.	R9	N.P.D.
NEO BASALT naturale	α da 11° a 19°	> 0,4	R10	N.P.D.
NEO BASALT grip	α da 20° a 27°	> 0,4	R11	N.P.D.
SENSO DI MARMO	N.P.D.	> 0,4	N.P.D.	N.P.D.
BASALTINA	N.P.D.	N.P.D.	N.P.D.	N.P.D.
CEMENT	N.P.D.	N.P.D.	N.P.D.	N.P.D.
WOOD STONE	N.P.D.	N.P.D.	N.P.D.	N.P.D.

